


TOPCOAT TPU 240

Driving rain proof. Open to diffusion. Time saving through integrated self-adhesive seam. Can be used from DN >10°. Made of durable polyester fleece and TPU coating. Extremely versatile and heat-resistant.



application	roof membrane		
functional layer	polyurethane (TPU) coating		
carrier material	polyester fleece		
color	black		
basis weight	EN 1849-2	g/m ²	240 (±10)

PROPERTY	TEST	UNIT	VALUE
----------	------	------	-------

General characteristics

roll width	EN 1848-2	m	1,5
roll length	EN 1848-2	m	40
m ² per roll	EN 1848-2	m ²	60
weight roll	-	kg	14,4

Technical characteristics

behavior in case of fire	EN 13501-1	Class	E
resistance to water penetration	EN 1928	Class	W1
after artificial aging	EN 1297/1296	Class	W1
maximum tensile force MD/CD	EN 12311-1	N / 50mm	350/310
maximum tensile strength after aging MD/CD	EN 12311-1	%	75/75
elongation MD/CD	EN 12311-1	%	60/70
elongation after aging MD/CD	EN 1297/1296	%	50/60
tear resistance / nail shaft MD/CD	EN 12310-1	N / 200mm	270/250
cold bending behavior	EN 1109	°C	-30
sd value	EN ISO 12572	m	0,15
resistance to air passage	EN 12114	m ³ /(m ² /h/50Pa)	<0,01
temperature resistance	EN 13859-1	°C	-40 to +100
UV resistance	-	months	3
suitability as a material for temporary cover	-	months	3
ZVDH product data sheet - class	-	-	UDB-A / USB-A
Ö-Norm: B3661 – Table 5/4119 – Section 6.1.2	-	-	Type II

These values may have tolerances. Unless otherwise stated, industry standard, material and performance tolerances apply.